

Specifica tecnica

Modelli DC 12 ÷ 1545

Modello	Portata volumetrica ¹⁾	Punto di rugiada	Pressione ²⁾	Temperatura ambiente	Temperatura d'ingresso aria compressa	Dimensioni L x P x H	Peso	Connessione aria compressa / aria di rigenerazione	Alimentazione elettrica
	m³/min		bar	°C	°C	°C	mm	kg	
i.DC 16	1,60	-40	5 ... 16	+2 ... +45	+2 ... +50	750 x 750 x 1950	181	G ¾"	100-240 V ±10% / 1 Ph / 50 ... 60 Hz
i.DC 23	2,30					750 x 750 x 1950	220	G ¾"	
i.DC 34	3,40					1150 x 750 x 1970	308	G 1½"	
i.DC 52	5,20					1150 x 750 x 1980	398	G 1½"	
i.DC 67	6,70					1150 x 750 x 1980	421	G 1½"	
i.DC 84	8,40					1150 x 750 x 1990	531	G 2"	
i.DC 115	11,5					1150 x 750 x 1990	650	G 2"	
i.DC 140	14,0					1150 x 750 x 2000	815	G 2"	
i.DC 175	17,5		5 ... 11			1500 x 1320 x 1910	965	DN 80	
i.DC 225	22,5					1500 x 1420 x 1930	1275	DN 80	
i.DC 275	27,5					1500 x 1470 x 2090	1525	DN 80	
i.DC 330	33,00					1500 x 1520 x 2125	1710	DN 80	
i.DC 395	39,5					1500 x 1720 x 2146	2080	DN 100	
i.DC 450	45,0					1700 x 1770 x 2225	2305	DN 100	
i.DC 610	61,0					1950 x 1920 x 2258	2755	DN 150	
i.DC 870	87,0					2400 x 2140 x 2456	4105	DN 150	
i.DC 1190	119,0					2690 x 2335 x 2701	6200	DN 200	
i.DC 1555	155,5					2820 x 2504 x 2536	6800	DN 200	